



NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)

- 1. BRASS PER QQ-B-626
- 2. BRASS PER QQ-B-613
- 3. PHOSPHOR BRONZE PER QQ-B-750
- 4. TEFLON MIL-P-19468
- 5. NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
- 6. GOLD PL. 3 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE

15	LOCK RING	NOTE 1	NOTE 6	1	S931-750-3
14	NUT	NOTE 1	NOTE 5	1	RN108-9-05X23S
13	COVER	NOTE 2	NOTE 5	3	CV-895X07-T
12	RESISTOR	766R		1	RS-766R-1/8W -1%
11	INSULATOR	NOTE 4	NATURAL	2	15687062401-10
10	PIN	NOTE 1	NOTE 6	1	15687062401-9
9	CONTACT PIN	NOTE 3	NOTE 6	1	15687062401-8
8	INSULATOR	NOTE 4	NATURAL	1	15687062401-7
7	BODY	NOTE 1	NOTE 6	1	15687062401-6
6	HOUSING	NOTE 1	NOTE 5	1	15687062401-5
5	CONTACT PIN	NOTE 1	NOTE 6	2	1564077A1-5
4	INSULATOR	NOTE 4	NATURAL	2	1562076A1-4-B
3	BODY	NOTE 1	NOTE 5	2	1562076A1-3
2	OUT CONTACT	NOTE 3	NOTE 6	2	1561121G1-2
1	SHELL	NOTE 1	NOTE 5	2	1561121G1-1
NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO

DIMENSIONS ARE IN MILLIMETERS
UNLESS OTHERWISE SPECIFIED
TOLERANCES
0.5-6 = ±0.2
6-30 = ±0.4
30-120 = ±0.6
120-315 = ±1
315-1000 = ±1.6
1000-2000 = ±2.4

PART NO.	1564077A1-N/3GT3G-75
APPROVED	DATE 10-11-01'
CHECKED	DATE 10-11-01'
DRAWN	DATE 10-11-01'

Amphenol	
TITLE 1.6-5.6 M-F-M Y-LINK	
DRAWING NO. KJ-1564077A1-N/3GT3G-75	
ITEM NO.	

SCALE	2.5/1	ISSUE	A	FILE NO
-------	-------	-------	---	---------