



REVISIONS		
ISS	ZONE	DESCRIPTION\PER REQUEST\DATE

REMARK:1. NO.6 MUST WITHSTAND A 6 lbs. MIN. PUSHOUT FORCE FROM NO.1 AFTER STAKING OPERATION
 2. REMARK1 IS MAINTAINED BY STAMPING THE FOUR POINTS SHOWN ON THE DRAWING WITHOUT PUNCTURING NO.1

NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)
 1. BRASS PER QQ-B-626
 2. GOLD PL. 3 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
 3. BERYLLIUM COPPER PER QQ-C-530
 4. GOLD PL. 50 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
 5. TEFLON MIL-P-19468

6	INSULATOR	NOTE 5	NATURAL	1	SMAF-SMBM1-2-C
5	CONTACT PIN	NOTE 3	NOTE 4	1	SMAF-MMCXM1-3-B
4	INSULATOR	NOTE 5	NATURAL	1	SMAF-MMCXM1-2-C
3	BODY	NOTE 1	NOTE 2	1	SMAF-MMCXM1-5-B
2	RETAINER RING	NOTE 3	NOTE 2	1	MMCX1121A1-5-C
1	HOUSING	NOTE 1	NOTE 2	1	SMAF-SMBM1-1
NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.

DIMENSIONS ARE IN MILLIMETERS		
UNLESS OTHERWISE SPECIFIED TOLERANCES		
0.5-6	= ±0.2	
6-30	= ±0.4	
30-120	= ±0.6	
120-315	= ±1	
315-1000	= ±1.6	
1000-2000	= ±2.4	
SCALE	6/1	ISSUE
FILE NO.		

PART NO. SMAF-MMCXM1-3GT50G-50		<h1>Amphenol</h1>
APPROVED	DATE 10-11-01'	
CHECKED	DATE 10-11-01'	
DRAWN	DATE 10-11-01'	
TITLE		SMA FEMALE TO MMCX MALE ADAPTOR
DRAWING NO.		KJ-SMAF-MMCXM1-3GT50G-50
ITEM NO.		